

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A hybrid lens comprising:

a spherical lens; and

an aspherical lens formed of plastic on at least one surface of the spherical lens;

wherein when c is a surface curvature (an inverse function of radius), ρ is a position on an optical surface in radial coordinates, k is a conic constant, and a_i is a polynomial coefficient defining the deviation from a spherical surface, a lens surface z of the aspherical lens satisfies the equation:

$$z = \frac{c \cdot \rho^2}{1 + \sqrt{1 - (1 + k) \cdot c^2 \cdot \rho^2}} + \sum_{i=2}^7 a_i \cdot \rho^{2i}.$$

2. (original): The hybrid lens of claim 1, wherein the aspherical lens is formed on at least one of an incidence surface and an emission surface of the spherical lens.

3. (original): The hybrid lens of claim 1, wherein the spherical lens is formed of glass.

4. (original): The hybrid lens of claim 1, wherein the spherical lens has a refractive index within a range of 1.45 – 1.95.

5. (original): The hybrid lens of claim 1, wherein the aspherical lens has a refractive index within a range of 1.45 – 1.8.

6. (original): The hybrid lens of claim 1, wherein the spherical lens and the aspherical lens have different refractive indexes.

7. (canceled).

8. (currently amended): A projection optical system comprising:
a hybrid lens that is positioned along an optical path between a fluorescent surface and a screen onto which light emitted from the fluorescent surface is projected to form an image and includes a spherical lens and an aspherical lens formed of plastic on at least one surface of the spherical lens;
a protective lens that covers the entire fluorescent surface;
a meniscus lens that is positioned along an optical path between the protective lens and the hybrid lens; and
a cooling liquid that is positioned between the protective lens and the meniscus lens.

AMENDMENT UNDER 37 C.F.R. § 1.111

U.S. Application No. 10/664,043

Attorney Docket No. Q75668

9. (original): The projection optical system of claim 8, wherein the aspherical lens is formed on at least one of an incidence surface and an emission surface of the spherical lens.

10. (original): The projection optical system of claim 8, wherein the spherical lens is formed of glass.

11. (original): The projection optical system of claim 8, wherein the spherical lens has a refractive index within a range of 1.45 – 1.95.

12. (original): The projection optical system of claim 8, wherein the aspherical lens has a refractive index within a range of 1.45 – 1.8.

13. (original): The projection optical system of claim 8, wherein the spherical lens and the aspherical lens have different refractive indexes.

14. (currently amended): The A projection optical system of claim 8, comprising a hybrid lens that is positioned along an optical path between a fluorescent surface and a screen onto which light emitted from the fluorescent surface is projected to form an image and includes a spherical lens and an aspherical lens formed of plastic on at least one surface of the spherical lens;

wherein when c is a surface curvature (an inverse function of radius), ρ is a position on an optical surface in radial coordinates, k is a conic constant, and a_i is a polynomial coefficient defining the deviation from a spherical surface, a lens surface z of the aspherical lens satisfies the equation:

$$z = \frac{c \cdot \rho^2}{1 + \sqrt{1 - (1 + k) \cdot c^2 \cdot \rho^2}} + \sum_{i=2}^7 a_i \cdot \rho^{2i}.$$

15-17. (canceled).

18. (original): The projection optical system of claim 8, wherein the hybrid lens is a correction power lens.

19. (original): The projection optical system of claim 8, further comprising at least one correction power lens that is positioned between the hybrid lens and the fluorescent surface, and refracts incident light.

20. (original): The projection optical system of claim 19, wherein the correction power lens has an aspherical surface.